

VALVOLE 3"



Con valvola pneumatica

Valvola ad elevate prestazioni in grado di pulire maniche di più di 10m di lunghezza a basse pressioni

CERTIFICAZIONI PRODOTTO

STANDARD



PED

SPECIFICHE TECNICHE VALVOLA

Caratteristiche		Valori
Uscita		Pipe 3"
Pressione di Esercizio		1,5-8 bar
Range Temperatura Standard		-40 °C ; +100 °C
Range Alta Temperatura		-20 °C ; +200 °C
Peso		12 kg
Grado di protezione (standard)		IP65
Classi purezza aria consigliati (ISO 8573-1)	Per Solidi	2
	Per Acqua con $T > +3^{\circ}\text{C}$	4
	Per Acqua con $-20^{\circ}\text{C} < T < +3^{\circ}\text{C}$	3
	Per Acqua con $-40^{\circ}\text{C} < T < -20^{\circ}\text{C}$	2
	Per Olio	1

LISTA COMPONENTI

No.	Descrizione	Materiale	Immagine
1	Screw M6	SS	
2	Washer Grover M	SS	
3	Cover 3/4"	Die Cast Alu	
4	Diaphragm 3/4"	TPE	
5	Screw M10	SS	
6	Washer	SS	
7	Cover 3"	Die Cast Alu	
8a	STD Diaphragm 3"	TPE	
8b	HT Diaphragm 3"	VITON+PTFE	
9	Body 3" Integrated	Die Cast Alu	
10	Body Pipe O'Ring	NBR	
11	Body Tank O'Ring	NBR	
12	Clamp Tank O'Ring	NBR	
13	Clamp 3"	Die Cast Alu	
14	Pipe Clamp O'Ring	NBR	
15	Washer 3"	Pa + Ela	
16	Blow Pipe 3"	CS or SS	
E	Optional Fitting	Nickeled Brass	

LAYOUT DIMENSIONALI

